



**ACCUWEIGH**

Onboard and Vehicle  
Weighing Systems

# LiftLog 100

The RDS Liftlog 100 is a cost-effective weighing and load monitoring instrument specifically designed for forklift trucks that displays the live weight and features visual and audible overload warning alarms.



## DESCRIPTION

The RDS Liftlog 100 is an operator friendly product that has been specifically designed for use on forklift trucks working in a despatch yard or warehouse environment.

Using a sensor to measure hydraulic pressure in the system, the Liftlog 100 informs the operator of load as a 'live' weight in tons or kg. In addition, when approaching and at the point of overload, an internal (and optional external) alarm will sound to further inform the operator of load status.

There is also the option of an external light bar to indicate load from 50% through to 110% of load capacity.

## FEATURES

- LCD Indicates Load as a "Live" Weight and Bar Graph of Load Status
- Accuracy  $\pm 2\%$  of Truck Capacity
- Single Button User Control (Reset to Zero) for Easy Operation
- Initial Audible Alarm at 90% of Permitted Load with Continuous Audible Alarm and Flashing Display at and in Excess of 100%
- Overload Logging Capability
- Quick and Easy Installation
- Proven Technology in a Robust Waterproof Enclosure Sealed to IP-67
- Unique Bracket Enables Installation of the Instrument in Any Position

## ADVANTAGES

- Increases Loading Safety in the Yard and/or Warehouse
- Value-Adding System for Minimal Investment
- Allows Correct and Even Loading of Storage and Vehicles
- Enables Check-Weighing of Incoming and Outgoing Goods
- Identifies Operators and Forklifts at Risk Through Memory Feature
- Increases Vehicle Efficiency
- Maintains Accuracy
- Promotes Best Operator Use
- Maintains Lifting Capacity and Driver Visibility
- Minimises Machine Downtime for Servicing or Repair
- Nationwide Service and Back Up from Accuweigh

## ENHANCEMENTS

- External audible alarm for use in noisy environments. A variety are available dependent on application.
- External light alarm for high visibility indication of load status.



## TECHNICAL DATA

Operating Voltage	10 - 30VDC
Temperature Range	-20° to +40°C
System Accuracy	$\pm 2\%$ of Truck Capacity
Sensor Range	0 - 250 Bar
Environmental Protection	Instrument Unit IP-67 Full RFI/EMI protection

## ALSO IN THE RANGE



- **Liftalert** for a load monitor with early warning of tip-over point.



- **Speed and Distance 200** for forklift speed and distance monitoring and speed limit alarms.

Accuweigh Pty Ltd

BROCHURE: AW386 | REVISION: H12

WESTERN AUSTRALIA (HEAD OFFICE):  
PHONE: (08) 9259 5535

SOUTH AUSTRALIA OFFICE:  
PHONE: (08) 8447 5011

NEW SOUTH WALES (SYDNEY) OFFICE:  
PHONE: (02) 9728 4877



[www.accuweigh.com.au](http://www.accuweigh.com.au)

VICTORIA OFFICE:  
PHONE: (03) 9548 5554

NEW SOUTH WALES (NEWCASTLE) OFFICE:  
PHONE: (02) 4966 8900

QUEENSLAND OFFICE:  
PHONE: (07) 3265 5520